



ENGINE TYPE	PISTON	PISTON RING	PISTON PIN	PIN BUSHING	LINER		LINER KIT SET
					FLANGED	NO FLANGE	
ZD30DDTI 2953 cc CABSTAR PATROL F24M Y61 2006-	Ø 96.00 -18.2 CD 50.1 TL 78.1	1 - 2.5 HK 1 - 2.0 1 - 2.0	Ø 33.000 TL 78.00 		TL 165.0 OD 100.0 FT 5.0 FD 104.0	160.0 100.0	TEIKIN NO. LKSF 44678AG LKXS 44678AG
	TEIKIN NO. 44678AG	TEIKIN NO. R 44673	TEIKIN NO. P 44297	TEIKIN NO. B 44297	TEIKIN NO. LSF 44672 LSX 44672		
Surface Treatment Tin Coated	Bore Clearance MRC: 0.050 mm MP: 8.50 mm	REFERENCE NO. 12010-DB000 12010-DB010	REFERENCE NO. 12033-DB010 12033-VK610	REFERENCE NO. 12030-1W400 12030-2W200	REFERENCE NO.		

How To Read The Above Catalog Data

ENGINE TYPE	PISTON	PISTON RING	PISTON PIN	PIN BUSHING	LINER		LINER KIT SET
					FLANGED	NO FLANGE	
1	Ø 2 CD TL	5	Ø 6 TL		7		TEIKIN NO.
	TEIKIN NO.	TEIKIN NO.	TEIKIN NO.	TEIKIN NO.	TEIKIN NO.		
	3				10		11
	REFERENCE. NO.	REFERENCE NO.		REFERENCE NO.	REFERENCE NO.		
Surface Treatment	Bore Clearance						
8	9	4					

<p>1</p> <ul style="list-style-type: none"> APPLICATION AND / OR ENGINE MODELS WITH YEARS OF APPLICATION. CAPACITY OF ENGINE IN CUBIC CENTIMETERS (CC). NUMBER OF CYLINDERS. 	<p>6</p> <ul style="list-style-type: none"> NOMINAL OUTER DIAMETER OF PISTON PINS. TL = TOTAL LENGTH OF PISTON PIN <p>CIRCLIP TYPES</p> <p>RECTANGULAR -X- SECTION TYPE CIRCULAR -X- SECTION TYPE</p> <p>7</p> <ul style="list-style-type: none"> TL = TOTAL LENGTH OF CYLINDER LINER IN MILLIMETERS. OD = OUTER DIAMETER OF CYLINDER LINER IN MILLIMETERS. FT = FLANGE THICKNESS OF CYLINDER LINER IN MILLIMETERS. FD = FLANGE DIAMETER OF CYLINDER LINER IN MILLIMETERS. <p>10</p> <ul style="list-style-type: none"> TEIKIN LINERKIT NUMBERING SYSTEM. PREFIX "LKSF" MEANS LINERKIT WITH SEMI-FINISHED AND NO FLANGE LINERS. PREFIX "LKXS" MEANS LINERKIT WITH SEMI-FINISHED AND FLANGED LINERS. PREFIX "LKFX" MEANS LINERKIT WITH FULLY FINISHED AND NO FLANGE LINERS. PREFIX "LKFF" MEANS LINERKIT WITH FULLY FINISHED AND FLANGED LINERS. PREFIX "LKCX" MEANS LINERKIT WITH CHROMED AND WITH NO FLANGE LINERS. PREFIX "LKCF" MEANS LINERKIT WITH CHROMED AND FLANGED LINERS.
<p>2</p> <ul style="list-style-type: none"> NOMINAL BORE DIAMETER. CD = COMPRESSION DISTANCE OF PISTON IN MILLIMETERS. PLUS VALUE DENOTES HEIGHT OF RAISED (ELEVATED) CROWN. MINUS VALUE DENOTES DEPTH OF DEPRESSED (CAVITATED) CROWN. TL = TOTAL LENGTH OF PISTON IN MILLIMETERS. 	<p>9</p> <ul style="list-style-type: none"> PISTON RING SIZES. SUFFIX "FK" REFERS TO FULL KEYSTONE TYPE RINGS. SUFFIX "MK" REFERS TO HALF KEYSTONE TYPE RINGS.
<p>3</p> <ul style="list-style-type: none"> TEIKIN NUMBER FOR PISTON. SUFFIX "A" REFERS TO PISTONS WITH ALFIN REINFORCEMENT. SUFFIX "G" REFERS TO PISTONS WITH COOLING TUNNEL (GALLERY). SUFFIX "AG" REFERS TO PISTONS WITH BOTH ALFIN AND GALLERY. <p>(SUPERSEDED NUMBERS ARE GIVEN IN PARENTHESIS.)</p> <p>4</p> <ul style="list-style-type: none"> REFERENCE NO. THESE NUMBERS REFER TO COMMONLY USED NUMBERS IN THE SPAREPARTS INDUSTRY. 	<p>11</p> <ul style="list-style-type: none"> TEIKIN LINERKIT NUMBERING SYSTEM. PREFIX "LKSF" MEANS LINERKIT WITH SEMI-FINISHED AND NO FLANGE LINERS. PREFIX "LKXS" MEANS LINERKIT WITH SEMI-FINISHED AND FLANGED LINERS. PREFIX "LKFX" MEANS LINERS ARE FULLY FINISHED AND NO FLANGE. PREFIX "LKFF" MEANS LINERS ARE FULLY FINISHED AND FLANGED. PREFIX "LKCX" MEANS LINERS ARE CHROMED AND NO FLANGE. PREFIX "LKCF" MEANS LINERS ARE CHROMED AND FLANGED.